



Floor Finish

A high solids, low odor, UHS floor finish that looks better longer. High Mileage^{TM/MC} floor finish delivers excellent gloss build and outstanding durability for your floors, even in the heaviest of traffic!

Less Recoat Cycles = Labor Savings

Extended recoat and stripping cycles yield labor savings and overall improved productivity.

High Performance and Durability

Specially designed higher solids formula builds durability over time. **High Mileage^{TM/MC}** floor finish is extremely tough in high traffic areas and resists dirt, black heel marks & scratches exceptionally well.

Low Odor Formula

Features a low odor profile – perfect for busy aisles, hallways, and other appropriate areas in 24-hour facilities.

Easy to Install

Install up to five coats in one night.



HIGH MILEAGE^{TM/MC} FLOOR FINISH

Profile

WHAT IS IT?	A high solids, lower odor, ultra high speed floor finish for low to medium frequency locations.
WHAT DO I USE IT ON?	Designed for use on all resilient floors. Prior to use on non-resilient surfaces like terrazzo, quarry tile or concrete, test HIGH MILEAGE ^{TM/MC} floor finish for adhesion. In some cases a JOHNSON WAX PROFESSIONAL non-resilient sealer may be required.
HOW DO I USE IT?	<p>PREPARATION: 1. Blockade areas to be stripped or finished. Floors will be very slippery until dry. 2. Strip floor, using a JOHNSON WAX PROFESSIONAL brand stripper per the instructions on the stripper label. 3. Apply 3 or more medium coats of finish using a clean finish mop. Apply additional coats until desired gloss is obtained. 4. Allow 30-45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24-hours before burnishing.</p> <p>MAINTENANCE: 1. Dust mop or sweep. 2. Clean the floor with a mop or an automatic scrubber using the recommended JOHNSON WAX PROFESSIONAL brand cleaner according to label directions.</p> <p>To enhance appearance, use any of the following methods: Dry buff using medium to aggressive pad and 1000-1500 rpm equipment. Ultra-high speed burnish using a medium aggressiveness pad and 2000+ rpm equipment.</p> <p>RECOATING: 1. Dust mop or sweep. 2. Clean the floor with a mop or an automatic scrubber using the recommended JOHNSON WAX PROFESSIONAL brand cleaner according to label directions. 3. Blockade area and apply 1-2 uniform coats of finish using a clean mop. 4. Allow finish to cure for 24 hours before burnishing.</p> <p>REMOVAL: 1. Remove using recommended JOHNSON WAX PROFESSIONAL brand stripper following label directions.</p>
PRECAUTIONS:	<ol style="list-style-type: none"> 1. Do not dilute. 2. Do not use on surfaces colder than 10°C/50°F. 3. To avoid contamination, do not return unused finish to original container. 4. Do not freeze.

Specifications

Dilution:	Ready-to-use
Non-volatile Solids:	25%
Color/Form:	White opaque liquid
Odor:	Mild
Drying Time:	35-45 minutes (under normal conditions)
pH:	8.25
Specific Gravity:	1.03
Slip Resistance:	Meets ASTM D2047 requirements for slip resistance

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDSs are available on line at www.johnsondiversey.com or by calling 1-888-352-2249.

Packaging

PACK / SIZE	PRODUCT CODE
1/5 gallon / 18.9 L BIB	4210179



Johnson wax
PROFESSIONAL

FOR COMMERCIAL & INDUSTRIAL USE ONLY

© 2006 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902. All Rights Reserved.

For further information on special applications or other Johnson Wax Professional products, contact your JohnsonDiversey representative, or call us at 1-800-558-2332 or visit our web-site at www.johnsondiversey.com

Printed in the U.S.A. on recycled paper containing 10% post consumer wastes.

SPC723 (06/048)