

## Suma Force

Aluminium safe, heavy duty degreaser

### Description

**Suma Force D3.5** is a concentrated liquid degreaser for the cleaning of heavily soiled surfaces in the kitchen.

### Key properties

**Suma Force D3.5** is an alkaline liquid detergent suitable for manual cleaning of all heavily soiled surfaces in the kitchen, like floors, equipment, cooker hoods and cooker tops. It is an optimal blend of non-ionic and anionic surfactants, for good wetting of surfaces.

**Suma Force D3.5** is also alkali and contains sequestrant for effective removal of all kinds of grease and dried-on food. The formulation is balanced in such a way that the product is safe for use on aluminium surfaces.

**Suma Force D3.5** is especially suitable for cleaning of floors either manually with a mop system or with low pressure spray equipment.

### Benefits

- Powerful formulation cuts through heavy grease and leaves surfaces clean and shiny
- Dissolves soil and holds it in solution, preventing re-deposition
- Formulated to be safe for use on aluminium
- Suitable for use in foaming equipment

### Use instructions

The recommended use concentration varies from 10-50 ml per litre of hand hot water, dependent on the soil level and application.

For controlled dosing the product can be used via the JohnsonDiversey QFM system.


### Cleaning Method – general:

1. Apply solution (10-20ml/L) to surface with cloth, pad or low pressure spray equipment
2. Clean with cloth or brush
3. Rinse with clean water and allow to air dry
4. Soak if necessary

### Floor cleaning:

- With mop system
  1. Dilute product (10-30 ml/L) in hot water
  2. Apply solution with mop
  3. Remove dirt with the mop
  4. Rinse with clean water and allow to air dry

# D3.5



## Suma Force

### Fryer cleaning:

- Weekly clean:
  1. Drain oil and close valve
  2. Fill with hot solution (50ml/L) of **Suma Force D3.5** to almost oil fill level
  3. Allow 10 – 15 minutes contact time; scrub sides before draining
  4. Scrub remaining residues from side walls and heating elements with a scourer pad or brush
  5. Rinse twice with clean, hot water and allow to air dry
- Periodic deep clean:
  1. Drain oil and close valve
  2. Fill with hot solution (50ml/L) of **Suma Force D3.5** to almost oil fill level
  3. Turn on fryer and bring to controlled boil for 15 minutes; scrub sides before draining
  4. Scrub remaining residues from side walls and heating elements with a scourer pad or brush
  5. Rinse twice with clean, hot water and allow to air dry

### Technical data

Appearance:	Clear yellow liquid
pH neat:	12.8
pH 1% solution:	11.0
Relative density (20°C):	1.10

These figures are typical values and should not be interpreted as specifications.

### Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

Store in original container. Avoid extremes of temperature.

### Product compatibility

Under recommended conditions of use, **Suma Force D3.5** is suitable for use on materials commonly encountered in the kitchen including aluminium.

### Available pack sizes

Article code	Pack size	Pack type
7512054	2 ×5L	

**JohnsonDiversey** (UK)  
Weston Favell Centre  
Northampton NN3 8PD  
Tel. 01604 405311  
[www.johnsondiversev.com](http://www.johnsondiversev.com)