



Undercover^{TM/MC} Floor Sealer

A specially formulated sealer to improve the adhesion and performance of floor finishes on rubber flooring.

Part of a comprehensive rubber floor care program solution which properly strips, seals and cleans rubber floors

Extends the Life of New and Older Rubber Flooring

- Seals and protects
- Provides better adhesion and leveling for floor finishes

Saves Stripper Time and Labor

- Easily removed with RubberSAFE^{TM/MC} Rubber Floor Stripper

Compatible with Traditional Floor Care Programs

Designed For

HEALTHCARE

EDUCATION

ATHLETIC ARENAS



Use Overview:

Undercover™/MG Floor Sealer is specially formulated to seal and protect resilient and hard floor surfaces. This product provides a clear, non-yellowing base coat for better adhesion, leveling and gloss when applying floor finish.

Use on resilient floors such as vinyl, vinyl composition, vinyl asbestos, rubber, linoleum and asphalt tile. Not recommended for use on wood, cork or non-resilient floors such as concrete or terrazzo.

PREPARATION

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floor, using per the instructions on the stripper label.

COATING

- Apply 1-2 uniform coats using a clean mop. Apply additional coats until desired gloss is obtained.
- Allow 30-45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

BURNISHING

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended cleaner according to label directions.
- Burnish using appropriate pads.

RECOATING

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended cleaner according to label directions.
- Blockade area and apply 1-2 uniform coats of finish using a clean mop.
- Allow finish to cure for 24 hours before burnishing.

FOR BEST RESULTS

- Do not dilute.
- Do not use on surfaces colder than 50°F / 10°C.
- To avoid contamination, do not return unused finish to original container.
- Not intended for use on wood floors.

COVERAGE

- 2000-2500 sq. ft. per U.S. gallon.

DRY TIME

- 30-45 minutes.



NOTE: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Not intended for use in indoor areas.

Meets ASTM D-2047 requirements for slip resistance.

Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS's are available online at www.johnsondiversey.com or by calling 1-888-352-2249.

Product Specifications:

| | |
|----------------------------|--------------------|
| Dilution | Ready-to-use |
| Color / Form | Off-white liquid |
| Solubility in water | Complete |
| Flash Point | >200° F (>93.3° C) |

| | |
|-------------------------|--------------|
| pH | 8.3 |
| Specific Gravity | 1.03 |
| Fragrance | Mild ammonia |
| Shelf Life | 2 years |

Two convenient sizes for any size rubber floor:

| PRODUCT CODE | DESCRIPTION | PACKAGE SIZE |
|--------------|----------------------------------|--------------|
| 4955592 | 1 gallon (3.78 L) | 4 x 1 gallon |
| 4955605 | 5 gallon Envirobox™/MG Container | 1 x 5 gallon |

Hazard Rating:

| HMIS | | NFPA |
|------|--------------|------|
| 1 | Health | 1 |
| 0 | Flammability | 0 |
| 0 | Reactivity | 0 |

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

For additional information, please visit: www.johnsondiversey.com/rubberfloorcare