



Floor Stripper

Delivers fast, consistent removal of floor finish, saving you time & money.

Power To Deal With The Toughest Challenges

FASTRIP^{TM/MC} stripper delivers pure power performance, even on heavy build-up. It provides fast, consistent results and significantly reduces the chance of costly "do-overs."

Power Without The Odor

Provides low odor to meet the needs of health care and other 24/7 facilities.

One Stripper For All Tasks

FASTRIP stripper is highly concentrated and delivers powerful stripping performance across a wide range of dilutions. Pick the dilution that matches your stripping challenge.

Our Customers Agree – FASTRIP Saves Money!

A Service Contractor in Iowa told us, "FASTRIP floor stripper is some of the most powerful stuff we've seen. It took off 12 coats of floor finish in only one pass. We estimated a 50% time savings versus our current stripper. When a product saves that much time, it's clearly a winner."



Johnson wax
PROFESSIONAL

FASTRIP^{TM/MC} FLOOR STRIPPER

Profile

WHAT IS IT? FASTRIP^{TM/MC} floor stripper is a totally new concept in floor strippers. It delivers fast, consistent removal of floor finish even when dealing with heavy finish build-up. Since this solution is highly concentrated, it can be diluted to meet all your floor finish removal challenges. Plus, it's low odor! This solution will save time, money and it deals with all your floor removal challenges, quickly and effectively.

WHAT DO I USE IT ON? For use on VCT, vinyl, terrazzo, slate, ceramic and concrete floors that are sealed with floor finish.

HOW DO I USE IT? 1. Use appropriate personal protective equipment. Dilute FASTRIP^{TM/MC} floor stripper according to the chart below:

| No. of Coats on Floor | Recommended Dilution Ratios |
|-----------------------|-----------------------------|
| 1-5 | 1:12 - 1:18 |
| 6-10 | 1:9 - 1:12 |
| 11+ | 1:6 |

NOTE: When stripping 11+ coats of finish, use stripping brushes to eliminate clogging of stripping pads. 2. Blockade areas to be stripped. Floors will be very slippery until dry. Use ZORBA^{TM/MC} Absorbent Control Pad to help contain solution within area being stripped. 3. Apply a liberal amount of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water. 4. Let solution dwell according to the chart below:

| No. of Coats on Floor | Dwell Time |
|-----------------------|------------|
| 1-5 | 5-10 min. |
| 6-10 | 10 min. |
| 11+ | 10+ min. |

NOTE: Do not allow solution to dry on floor - add more solution as needed. 5. Machine or hand scrub thoroughly using black pad or stripping brush. While scrubbing floors with 11+ coats of finish, it may be necessary to apply water to aid with pickup of stripper/finish solution. 6. Pick up all of the stripper/finish solution with a clean mop, wet vac, or auto scrubber. When dealing with extreme build-up (11+ coats), repeat process if necessary. 7. Rinse floor with clean water to remove any residue not picked up by wet vac or auto scrubber. 8. Let floor dry completely before applying recommended JOHNSON WAX PROFESSIONAL brand floor sealer or finish.

CAUTIONS: Do not use on wood, linoleum, rubber, or marble floors or painted surfaces, as this product may harm these surfaces. Test for softening or color bleeding on asphalt floors before using. Do not use for selective stripping of finish on JOHNSON WAX PROFESSIONAL TECHNIQUE[®] or JONSEAL[®] 220 floor sealers.

Specifications

Specific Gravity: 1.08

Flash Point: Greater than 200° F

Shelf Life: 2 years.

HMIS Hazard Ratings:

| | Concentrate |
|-------------------|-------------|
| Health..... | 3 |
| Flammability..... | 0 |
| Reactivity..... | 0 |

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDSs are available on-line at www.johnsondiversey.com or by calling 1-888-352-2249.

Packaging

| PACK / SIZE | PRODUCT CODE |
|----------------------------------|--------------|
| 4 / 1 Gallon (3.78 L) Containers | 4122398 |
| 1 / 5 Gallon (18.9 L) Container | 4122401 |



Johnson wax
PROFESSIONAL

FOR COMMERCIAL & INDUSTRIAL USE ONLY

© 2005 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902.

For further information on special applications or other Johnson Wax Professional products, contact your JohnsonDiversey representative, at 1-800-558-2332 or visit our web-site at www.johnsondiversey.com.