



FrescoMax™/MC

Low Odor Floor Finish

Features a low odor profile without sacrificing performance.

The floor finish solution for use in facilities where odor is a concern.

Excellent Performance

- 25% solids formula produces high gloss build
- Excellent mark and scratch resistance profile

Ease of Maintenance

- Easy to apply finish
- Responds well to spray buffing or UHS burnishing

HEALTHCARE
EDUCATION
OFFICE
RETAIL

FrescoMax™/MC



Johnson wax
PROFESSIONAL

Use Overview:

FrescoMax™^{TM/MC} Low Odor Floor Finish is a low odor high gloss, high solids (25%) floor finish that provides excellent durability. Responds very well to spray buffing or UHS burnishing. Low odor profile is perfect for facilities where odor is a concern.

- Apply product using a clean finish mop or applicator pad.
- Medium coats should be applied, with average coverage rate around 2,000 sq. ft/gal.
- Product should be compatible with most existing finishes if they are deep scrubbed before application.
- Apply 2-4 coats of product the first day of installation and 2-3 additional coats the next day depending on desired gloss level.
- Burnish or spray buff for great gloss response.



Product Specifications:

Dilution	Ready-to-use
Color / Form	Milky white opaque liquid
% Solids	25
pH	8.2

Specific Gravity	1.03
Slip Resistance	Meets ASTM D2047 requirements for slip resistance
Dry Time	Approximately 30–45 minutes

One convenient size:

PRODUCT CODE	DESCRIPTION	PACKAGE SIZE
4520476	5 gallon Envirobox™ ^{TM/MC}	1 x 5 gallon

Hazard Rating:

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS's are available online at www.johnsondiversey.com or by calling 1-888-352-2249.